

Технические характеристики:

Input	8 DVB-C/S/S2 FTA Tuner + 6 ASI input			
Tuner Section	DVB-C	Standard	J.83A(DVB-C), J.83B, J.83C	
		Input Frequency	30MHz-1000Mhz	
		Constellation	16/32/64/128/256 QAM	
	DVB-S	Input Frequency	950-2150MHz	
		Symbol rate	2-45Msps	
		Signal Strength	-65~-25dBm	
	DVB-S2	FEC Demodulation	1/2, 2/3, 3/4, 5/6, 7/8 QPSK	
		Input Frequency	950-2150MHz	
		Symbol rate	QPSK 1~45Mbauds 8PSK 2~30Mbauds	
		Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10	
		Demodulation Mode	QPSK, 8PSK	
Multiplexing	Maximum PID Remapping	128per input channel		
	Function	PID remapping (automatically or manually)		
		Accurate PCR adjusting		
		Generate PSI/SI table automatically		
Scrambling	Maximum simulcrypt CA	4		
	Standard	ETSI 101 197, ETSI 103 197		
	Connection	Local/remote connection		
Modulation	QAM Channel	4		
	Standard	EN300 429/ITU-T J.83A/B/C		
	MER	≥40db		
	RF frequency	30~999MHz, 1KHz step		
	RF output level	-20~0dbm(87~107 dbμV),0.1db step		
	Symbol Rate	5.0Msps~9.0Msps, 1ksps stepping		
	Constellation	16/32/64/128/256QAM		
		J.83A	J.83B	J.83C
		16/32/64/128/256QAM	64/256 QAM	64/256 QAM
	Bandwidth	8M	6M	6M
System	Local interface	LCD + control buttons		
	Remote management	Web NMS		
	Stream Out	4*MPTS over UDP out (RJ45, 1000M, Unicast/Multicast)		
	Language	English and Chinese		
	Software Upgrading	Web and USB		
General	Dimension (W*D*H)	482mm×300mm×44.5mm		
	Weight	3.7kg		
	Temperature	0~45°C (Operation) ; -20~80°C (Storage)		
	Power	AC 100V±10%/60Hz; AC 220V±10%, 50/60HZ		
	Consumption	25W		

System	Local interface	LCD + control buttons
	Remote management	Web NMS
	Stream Out	4*MPTS over UDP out (RJ45, 1000M, Unicast/Multicast)
	Language	English and Chinese
	Software Upgrading	Web and USB
General	Dimension (W*D*H)	482mm×300mm×44.5mm
	Weight	3.7kg
	Temperature	0~45°C (Operation) ; -20~80°C (Storage)
	Power	AC 100V±10%/60Hz; AC 220V±10%, 50/60HZ
	Consumption	25W